




NU300



MODEL	A	C	D	E	F	I	L	M	N	WEIGHT	POWER	SPEED	MAXIMUM FLOW	WITH VARIABLE SPEED	MAXIMUM FLOW
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]	[kW]	[m/s]	[m ³ /h]	[m/s]	[m ³ /h]
NU3025	2500	2975	1160÷1625	2275	300	1410	420	390	370	235	1.1	0.44	24	0.14÷0.5	27
NU3030	3000	3430	1355÷1960	2615	300	1550	420	390	370	250	1.1	0.44	24	0.14÷0.5	27
NU3035	3500	3935	1585÷2305	2955	300	1610	420	390	370	265	1.1	0.44	24	0.14÷0.5	27
NU3040	4000	4320	1815÷2645	3295	300	1710	420	390	370	280	1.5	0.44	24	0.14÷0.5	27
NU3045	4500	4870	1830÷3010	3655	300	2225	420	390	370	295	1.5	0.44	24	0.14÷0.5	27
NU3050	5000	5330	2035÷3350	4005	300	2225	420	390	370	330	1.5	0.44	24	0.14÷0.5	27
NU3055	5500	5790	2245÷3695	4345	300	2225	420	390	370	355	2.2	0.44	24	0.14÷0.5	27
NU3060	6000	6235	2470÷4000	4685	300	2445	420	390	370	375	2.2	0.44	24	0.14÷0.5	27
NU3065	6500	6690	2675÷4340	4990	300	2445	420	390	370	395	2.2	0.44	24	0.14÷0.5	27
NU3070	7000	7150	2885÷4675	5325	300	2445	420	390	370	415	2.2	0.44	24	0.14÷0.5	27

	HOPPER			B	G	H	O
	STANDARD			675÷875	1000÷1070	805	525
	LARGE			880÷1160	1300÷1370	1335	850
	REMOVABLE			680÷920	1000÷1070	805	525

