



# NU500



MODEL	A	C	D	E	F	I	L	M	N	WEIGHT	POWER	SPEED	MAXIMUM FLOW	WITH VARIABLE SPEED	MAXIMUM FLOW
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]	[kW]	[m/s]	[m <sup>3</sup> /h]	[m/s]	[m <sup>3</sup> /h]
NU5025	2500	2975	1160÷1625	2275	500	1410	620	390	570	255	1.1	0.44	40	0.14÷0.5	45
NU5030	3000	3430	1355÷1960	2615	500	1550	620	390	570	280	1.1	0.44	40	0.14÷0.5	45
NU5035	3500	3935	1585÷2305	2955	500	1610	620	390	570	305	1.1	0.44	40	0.14÷0.5	45
NU5040	4000	4320	1815÷2645	3295	500	1710	620	390	570	330	1.5	0.44	40	0.14÷0.5	45
NU5045	4500	4870	1830÷3010	3655	500	2225	620	390	570	355	1.5	0.44	40	0.14÷0.5	45
NU5050	5000	5330	2035÷3350	4005	500	2225	620	390	570	380	1.5	0.44	40	0.14÷0.5	45
NU5055	5500	5790	2245÷3695	4345	500	2225	620	390	570	405	2.2	0.44	40	0.14÷0.5	45
NU5060	6000	6235	2470÷4000	4685	500	2445	620	390	570	430	2.2	0.44	40	0.14÷0.5	45
NU5065	6500	6690	2675÷4340	4990	500	2445	620	390	570	455	2.2	0.44	40	0.14÷0.5	45
NU5070	7000	7150	2885÷4675	5325	500	2445	620	390	570	480	2.2	0.44	40	0.14÷0.5	45

	HOPPER			B	G	H	O
	STANDARD			680÷920	1200÷1275	805	525
	LARGE			880÷1160	1500÷1575	1335	850
	REMOVABLE			680÷920	1200÷1275	805	525

